

Bei mir hat es wie folgt geklappt:

Alles über Putty:

Master:

```
sudo iobroker setup custom
Type of objects DB [file, couch, redis], default [file]: ENTER
Host of objects DB(file), default[127.0.0.1]: <0.0.0.0>
Port of objects DB(file), default[9001]: ENTER
Type of states DB [file, redis], default [file]: ENTER
Host of states DB (file), default[0.0.0.0]: ENTER
Port of states DB (file), default[9000]: ENTER
Host name of this machine [hostname]: ENTER
```

Slave:

```
sudo iobroker setup custom
Type of objects DB [file, couch, redis], default [file]: ENTER
Host of objects DB(file), default[127.0.0.1]: <ip adresse="">vom Hauptsystem
Port of objects DB(file), default[9001]: ENTER
Type of states DB [file, redis], default [file]: ENTER
Host of states DB (file), default[cubie]: <ip adresse="">vom Hauptsystem
Port of states DB (file), default[9000]: ENTER
Host name of this machine [hostname]: ENTER</ip></ip>
```

Master:

```
sudo iobroker multihost enable
```

Password vergeben und dann Neustarten

Slave:

```
sudo iobroker multihost browse
```

```
Master gefunden
```

```
sudo iobroker multihost connect
```

Password eingeben und dann Neustarten

Geht!